

# ELEVAH® 70

The Elevah 70 is the aerial platform equipped with a big basket, which has a capacity of 200 kg. It reaches 7 m working height.



Safety is ensured during any type of work at height (maintenance, inspection, assembly, etc ...)



The emovable control allows the platform to be raised from the ground.

## SOME ACCESSORIES AND CUSTOMISATION



**AT 10.1:** Power Batteries 12V wit Power connection to the Tractor.

➤ **OTHER ACCESSORIES AND COSTUMISATION ON P. 46**



By using stabilizers and positioning the cage 70 cm above ground level, a working height of 7 m can be reached.

ELEVAH 70

PUSH AROUND MACHINE



# ELEVAH<sup>®</sup> 70

|   | Without Stabilizers                | With Stabilizers                      |
|---|------------------------------------|---------------------------------------|
| Max. working height   | 6 m<br>(With basket in position 2) | 7,25 m<br>(With basket in position 2) |
| Max capacity  | 200 kg                             |                                       |
| Number of people  | 1                                  |                                       |
| Use   | Internal                           |                                       |
| <b>A</b> Closed machine height                              | 1700 mm                            |                                       |
| <b>B</b> Minimum platform height                            | 380 mm                             |                                       |
| <b>C</b> Height from ground to walk-on floor                | 970 mm                             |                                       |
| <b>D</b> Maximum platform height                            | 4000 mm                            | 5250 mm*                              |
| <b>E</b> Base overall dimensions                            | 1320 mm                            | 1380 mm                               |
| <b>F</b>  | 780 mm                             | 1350 mm                               |
| <b>G</b> Cage dimensions                                    | 780 mm                             |                                       |
| <b>H</b>  | 850 mm                             |                                       |
| <b>I</b>  | 0 mm                               | 40 mm                                 |
| <b>J</b> Max. distance from the wall                        | 0 mm                               | 300 mm                                |
| <b>K</b> Fixed picking tray dimensions                      | 760 mm                             |                                       |
| <b>L</b>  | 440 mm                             |                                       |
| Fixed picking tray capacity                                 | 20 kg                              |                                       |
| Machine weight with outriggers, 24V power supply            | 430 kg                             |                                       |
| Machine weight with stabilisers (power supply 220V 50/60Hz) | 400 kg                             |                                       |
| 24V power supply 2 Pb Acid batteries 12V                    | 105 Ah                             |                                       |
| 24V power supply - Battery charger                          | 110V - 220V                        |                                       |
| Swivel wheels dimensions (fixed)                            | Ø 200 x 50 mm                      |                                       |
| Swivel wheels dimensions                                    | Ø 150 x 45 mm                      |                                       |
| Max. speed (rising)   | 0,2 m/s                            |                                       |
| Max. speed (descending)                                     | 0,15 m/s                           |                                       |
| <b>L</b> Maximum pressure for wheel at full load**          | 2,0 kN                             |                                       |
| <b>L</b> Maximum pressure for stabilizer at full load**     | 2,2 kN                             |                                       |
| Work cycles (with fresh batteries)***                       | 200                                |                                       |

\* Max H. reached with cage at height -C-

\*\* Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).

\*\*\* By work cycle we mean a self-propelled movement of 20 m with a full ascent to and descent from the maximum height and with adjustment of the loading platform.

  Compliant with **EN280** rule.  
Approved for indoor use or outdoor use in the absence of wind.

