

ELEVAH® 40 B



The **manual traction** platform Elevah 40B allow you to work up to 4 m in safety.



ELEVAH 40B

PUSH AROUND MACHINE



Complies with EN 280 and is approved for internal use in the absence of wind.



ELEVAH[®] 40 B

Max. working height		4,00 m
Max capacity		150 kg
Number of people		1
Use		Internal
A	Closed machine height	1450 mm
B	Minimum platform height	300 mm
C	Maximum platform height	1930 mm
D		995 mm
E	Base overall dimensions	660 mm
F		740 mm
G	Cage dimensions	680 mm
H		740 mm
Machine weight		156 kg
Driving (steering) wheel size		Ø 100 x 30 mm
Swivel wheels dimensions (fixed)		Ø 150 x 45 mm



PERFORMANCE

Power supply	Electrical
Batteries	2 AGM 12V 35 Ah*
Battery charger	110 V - 220 V
Internal turning radius	0
External turning radius	1100 mm
Max. speed (rising – descending)	0,10 - 0,16 m/s
Work cycles (with fresh batteries) **	Ca. 125

* Optional 40BGM

** By work cycle we mean a self-propelled movement of 20 m with a full ascent to and descent from the maximum height and with adjustment of the loading platform.



Compliant with **EN280** rule.
Approved for indoor use or outdoor use in the absence of wind.

