

# ELEVATOR<sup>®</sup> 40 B

Max. working height		4 m
Max capacity		200 kg
Number of people		1
Use		Internal
<b>A</b>	Closed machine height	1730 mm
<b>B</b>	Min. height from the ground*	290 mm
<b>C</b>	Maximum platform height	1950 mm
<b>D</b>	Base overall dimensions	1000 mm
<b>E</b>		715 mm
<b>F</b>	Cage dimensions	685 mm
<b>G</b>		580 mm
Machine weight		265 kg
Idle front wheel size		Ø 125x35
Idle rear wheels size		Ø 150x40

## PERFORMANCE

Power supply		24 V
Batteries		2 AGM 12V 45 Ah
Battery charger		115V–230V 50/60HZ
<b>H</b>	Maximum climbing ability	15%
Internal turning radius		0
<b>R</b>	External turning radius	860 mm
Max. speed (rising)		0,15 m/s
Max. speed (descending)		0,15 m/s
<b>I</b>	Maximum pressure for wheel at full load **	1,55 kN

\* There is an intermediate step.

\*\* Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).



CE and TUV certified and approved for internal use in the absence of wind. In assessing compliance, only those standards whose proposed measures have been implemented were considered and only if a corresponding risk does indeed exist.

exist.

